Product Guide

LUSSO INTELLISMART Wall Hung Rimless Toilet Bidet inc. Cistern and Chrome Flush Plate

LUSSO TECHNOLOGY YOU CAN TRUST

FEATURES

- 1. Slim and smart design with the seat cover height of only 50mm.
- 2. Work with customised ceramic and available with wall-hung and back-to-wall toilets.
- 3. Adjustable water/air temperature and water flow.
- 4. SUS304 washing pipe with antibacterial nozzle, self-cleaning.
- 5. Adjustable position of the washing nozzle with pulsating and oscillating massage.
- 6. Air deodorisation.

LED nightlight design

Soft close seat cover with quick release function.

- 1. With rimless toilet.
- 2. With water heating mode of storage tank and performance of air gap and back flow prevention to confom to EN1717 standard.
- 3. CE certification.





Lusso Intellismart | Wall Hung Rimless Toilet Bidet



Happy hygiene



Instant wellness



1. CLEAN

Self-cleaning glazed toilet

Different from normal glaze toilet, self-cleaning glazed toilet is easier for cleaning, and not easy to stick dirt.

Rimless toilet

From now on, there is no place for dirt ans germs to hide, making a more attractive, more hygenic toilet.

Vortex flushing system

Only 3 seconds to instant cleaning through two-way 180° flush, vortex flushing system delivers a powerful action every time it is triggered.





2. CARE



3. COMFORT



6

QUICK RELEASE DESIGN FOR SEAT AND COVER



The toilet lid and cover can easily be removed, cleaned and remounted.

Take off



90° quick release

OVERVIEW



DIMENSIONS - WALL HUNG BIDET



Please note that all dimensions are provided in millimetres.

DIMENSIONS - CISTERN



Front view



Side view



Top view



DIMENSIONS - FLUSH PLATE



Front view

Side view

Ŀ

TECHNICAL SPECIFICATION

Water supply connector	G 3/8
Adaptable rated voltage	AC220-240, 50/60HZ
Electric power	950W
Power cord length	1.8m
Applicable water supply pressure range	0.07~0.75MPa(0.7~7.5Bar)
Applicable water supply temperature	4~35℃
Ambient temperature	4~40°C
Waterproof rate	IPX4
Water flow rate	350~650mL/min
Water temperature	31~39°C
Washing cycle	3 minutes
Water heating mode	Storage Tank
Maximum heater power	1200W
Safety device of the washing	Thermal cutoff fuses/ Liquid level switch/Thermostat
Back flow Prevention	Air Gap
Maximum air speed	5m/s
Maximum dryer power	280W
Drying cycle	3 minutes
Warm air temperature	35~50°C
Safety device of the drying	Thermal cutoff fuses/Thermostat
Deodorant method	Diatom pure
Deodorization cycle	15 minutes
Other safety device	Residual Current Devices

FUNCTION LIST

Rear Wash	
Lady Wash	•
Oscillating Massage	•
Pulsating Massage	•
Oscillating and Pulsating Spray	•
Adjustable Water Temperature (5 steps)	•
Adjustable Water Flow Rate (5 steps)	•
Adjustable Spray Position (5 steps)	•
Air Drying	•
Adjustable Dryer Temperature (5 steps)	•
Deodoriser	•
Nozzle Self-Cleaning	•
Nozzle Manual-Cleaning	•
User Mode (2 users)	•
Night Light	•
Ambient Light	•
Self Closing Seat and Cover	•
Quick Release Seat and Cover	•
Body Knob	•
Remote Control	•
Rimless Toilet	•

Lusso Carbury House Eagle Court Preston Farm Industrial Estate Stockton-on-Tees TS18 3TB Email: info@lussostone.com Tel: 0203 370 4057 www.lussostone.com

LUSSO